



## MULTIFAN TUBE FANS - 'Q' LINE

THE MULTIFAN MOTOR IS SPECIFICALLY DESIGNED TO WITHSTAND THE EXTREME MOISTURE CONDITIONS OFTEN ENCOUNTERED IN VERTICAL INSTALLATIONS (I.E CHIMNEYS, DUCTS, ETC.).



### TUBE FAN INCLUDES:

ENERGY EFFICIENT MULTIFAN MOTOR, POLYPROPYLENE FAN BLADE, 3 CAST ALUMINUM MOTOR ARMS, 3 NYLON MOUNTING ADAPTERS AND STAINLESS STEEL HARDWARE FOR FASTENING THE NYLON MOUNTING ADAPTERS TO THE CHIMNEY WALL.

- NOTE:
- \* 3 YEAR MOTOR WARRANTY
  - \* 120 / 240 VOLT TUBEFANS MAY BE OPERATED ONE SPEED OR VARIABLE SPEED.
  - \* 36" TUBEFANS ARE VARIABLE DOWN TO 120 VOLT ONLY.

DIA.	MODEL	PART #	VOLT	C.F.M. @ 0.10" S.P.	BLADE R.P.M.	AMP. DRAW
------	-------	--------	------	------------------------	-----------------	--------------

12"	TF2E30Q	E50-6217Q	240	2040	3200	1.50
-----	---------	-----------	-----	------	------	------

10"	TF4E25Q	E50-6201Q	240	760	1600	0.60
12"	TF4E30Q	E50-6202Q	240	1340	1600	0.60
14"	TF4E35Q	E50-6203Q	240	2020	1600	0.90
16"	TF4E40Q	E50-6204Q	240	2780	1600	1.10
18"	TF4E45Q	E50-6205Q	240	3540	1600	1.40
20"	TF4E50Q	E50-6206Q	240	4540	1600	1.80
24"	TF6E63Q	E50-6208Q	240	6710	1000	2.90
24"	TF6E63QIE2	E50-6222Q	240	5330	1110	1.90
28"	TF6E71Q	E50-6212Q	240	7180	1000	3.20
36"	TF8E92Q	E50-6209Q	240	9800	800	3.60

10"	TF4E25Q	E50-6101Q	120	760	1600	1.10
12"	TF4E30Q	E50-6102Q	120	1340	1600	1.10
14"	TF4E35Q	E50-6103Q	120	2020	1600	1.80
16"	TF4E40Q	E50-6104Q	120	2780	1600	2.30
18"	TF4E45Q	E50-6105Q	120	3540	1600	3.00
20"	TF4E50Q	E50-6106Q	120	4540	1600	3.30

### TUBE FAN HARDWARE (included with Tube Fans)

PART#	DESCRIPTION
E52-4100	NYLON ADAPTER /W BOLT & NUT
E52-4101	ADAPTER HARDWARE (TO MOUNT ARM TO HOUSING)
INCLUDES;	E52-0103 5/16" - 18 X 1" ST.ST. HEX HEAD BOLT
	E52-0141 3/8" ST.ST. FLAT WASHER
	E52-0151 5/16" - 18" ST.ST. LOCKNUT
	E52-0154 5/16" ST ST LOCK WASHER