

J&D INDOOR/OUTDOOR CEILING FAN

THE MODEL CF60 CASABLANCA STYLE CEILING FAN HAS PASSED CUL WATER SPRAY AND CORROSION TESTING. PERFECT FOR GREENHOUSE, AGRICULTURE AND ALL HIGH HUMIDITY AREAS. THE 60E MODEL IS ECONOMICALLY PRICED FOR COMMERCIAL AND INDUSTRIAL APPLICATIONS. BOTH MODELS ARE VARIABLE SPEED CONTROLLABLE AND HAVE A REVERSE SWITCH ON THE FAN TO CHANGE DIRECTION.

2 YEAR WARRANTY



115 VOLT C/W 16" CORD, 10" DOWN ROD

DIA.	PART#	SPEED	AMPS	CFM	
60"	ECF60A	VARIABLE	0.74	9,415	
N/A	ECN5	VARIABLE SPEED CONTROL (UP TO 4 FANS)			

(FOR HIGH HUMIDITY)

J&D WIDE GUARD HAF PANEL FAN

DIRECT DRIVE VARIABLE SPEED 115/230V MOTORS C/W POLY PROP IN FIBERGLASS PANEL FRAME. BUILT IN INDUSTRIAL LOOPS ON THE REAR OF FAN ALLOWS YOU TO ATTACH CHAIN OR CABLE TO HANG FAN STRAIGHT OR AT AN ANGLE. **2 YEAR WARRANTY**

DIA.	PART#	HP	AMP	CCFM	THRUST CFM
20"	EVPP20F13P	1/3	3.2/1.6	5,180	3680
24"	EVPP24F13P	1/3	3.2/1.6	6,020	4250



J&D SHADE POLE BLOWERS (INFLATION FANS)

DESIGNED FOR USE IN DOUBLE SIDED POLY GREENHOUSES. BOTH MODELS HAVE ADJUSTABLE DAMPER DOORS TO ADJUST AIR FLOW AS POLY EXPANDS IN HEAT OR SMALL HOLES DEVELOP. MOTORS HAVE THERMAL OVERLOAD PROTECTION. **1 YEAR WARRANTY**



PART#	CFM	AMP	FLANGE
EVBM60A-P	60 CFM	0.15	ROUND FLANGE 2-1/8" OPENING
EVBMBRKT-RND	-	-	INFLATION FAN BRACKET - ROUND
EVBM148A-P	148 CFM	0.50	SQUARE FLANGE 3-1/4"X2-1/8" OPENING
EVBMBRKT-SQ	-	-	INFLATION FAN BRACKET - SQUARE

J&D GALV. PORTABLE DRUM FAN

HEAVY DUTY G90 GALVANIZED HOUSING, POWDER COATED WIRE GUARDS MEETS OSHA REQUIREMENTS. FULLY ASSEMBLED WITH RUBBER FEET AND 8" HARD PLASTIC WHEELS. 10FT-120V CORD C/W OFF/ON SWITCH. **2 YEAR WARRANTY**

DIA.	PART#	HP	AMPS	SPD/DRIVE	CFM
36"	EVI3612WG	1/2	7	1SPD, DD	11,800
42"	EVI4234WG2	3/4	9.1/4.8	2SPD, BD	14,400/10,015
48"	EVI481WG	1	9.6	1SPD, BD	23,500



SEE www.jdmfg.com FOR MORE INFO ON J&D PRODUCTS