

GENIUS i-TOUCH SERIES 10" TOUCH SCREEN




These controllers have been built specifically for harsh livestock environments, and come equipped with our field proven modular hardware and software which is already used in existing GENIUS controllers.

Available in a multitude of models, the modular design of the GENIUS iTouch series permits easy and cost effective maintenance of your controllers, while providing the flexibility to grow and evolve according to your ever-changing needs

Remote access, monitoring, data logging and management

The GENIUS iTouch series amounts to much more than high performance controllers when teamed up with the FarmQuest online management service. Together, they make for a powerful management tool that you can access from anywhere in the world. Your controllers are connected to the FarmQuest server, which constantly uploads data and enables you to easily view, analyze and compare results with those of current or previous production batches. eForm reports selected by the producer can be sent to selected individuals, suppliers, and professionals in order



CALL FOR ASSISTANCE AND CONTROL LAYOUT

MORE INFO

GENIUS i-TOUCH SERIES 10" TOUCH SCREEN 8 ROOM MULTIZONE FOR FARROWING AND NURSERY ROOMS

As a recognized leader in smart controllers aimed at the agricultural sector, Monitrol greatly facilitates remote livestock management for all types of animal production through the FarmQuest application.

- The world-renowned iTouch series allows for real-time access and 24/7 management of farm installations
- Cutting-edge technology facilitating the management of ambient air (ventilation, heating, humidity, static pressure, CO2, etc.), animal populations, feed levels/consumption, lighting, and more
- Your yearly historical and current data is accessible to simplify report management and communication with your stakeholders
- 100% FarmQuest compatible, this cloud-based system is essential in optimizing your production efficiency!



PART #	MODEL #	DESCRIPTION
MASTER		
E53-3050	GE-ST10iV8ZP/10	10" i-TOUCH, 11MGCB, 10 ON/OFF, 8 ZONES


MODULES

E53-3060	GE-MOD444/S	MODULE 4 INPUTS, 4 VARIABLE, 4 ON/OFF, SWITCH
E53-3061	GE-MOD448/S	MODULE 4 INPUTS, 4 VARIABLE, 8 ON/OFF, SWITCH
E53-3062	GE-MOD424/S	MODULE 4 INPUTS, 2 VARIABLE, 4 ON/OFF, SWITCH
E53-3063	GE-MOD428/S	MODULE 4 INPUTS, 2 VARIABLE, 8 ON/OFF, SWITCH
E53-3043	X1314/R4	RELAY BOARD WITH 4 RELAYS
E53-3045	X1469/GE-MOD448/S	MAIN BOARD FOR GE-MOD

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel co. exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm

, ON, N0M-1S3
1-866-335-1431
www.exaconinc.ca

EN



sts,
pricing and



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

Genius iTouch Series / 10" Touch Screen

One super zone or up to 4 zones amongst which the available inputs and outputs are divided.

The iTouch Control system will consist of one master control combined with optional slaves, modules and optional boards to provide a complete ventilation system.

Also feeders, feed augers, water meters, poultry scales, bin scales and lights can be assigned to one or more zones. The Genius iTouch control has **built in adapter** to enable access to the FarmQuest where you can **manage your operation from anywhere internet is available from your PC or Smart phone.**

Exacon has created two models, base model from which you can add optional boards to suit your application or a deluxe model with optional boards pre-installed to give you many more features and capacity. Both models can be one large zone, two zone or even up to 4 zones.

iTouch Master Control Models: Deluxe Model Kit

(mostly suited for poultry applications)

PART #	MODEL	DESCRIPTION
E53-3030	GE-430izK/10MZ	4 VARIABLE, 30 OFF/ON RELAYS, 1 PROBE
E53-3031	GE-425izK/10MZ	4 VARIABLE, 25 OFF/ON RELAYS, 1 PROBE
E53-3032	GE-420izK/10MZ	4 VARIABLE, 20 OFF/ON RELAYS, 1 PROBE
E53-3033	GE-415izK/10MZ	4 VARIABLE, 15 OFF/ON RELAYS, 1 PROBE

This deluxe model includes the following input and communication boards X1199, X1201, X1205 8 pot. board, X1276, X1399 boards (8 input configurable). Also includes 12 communication ports for various options.

The deluxe model will then provide the following possible options by adding just the required hardware or items:

- 10 temperature inputs or up to 16*
- 4 duration sensors inputs (current sensor for feed) or up to 12*
- 4 pulse count input (water meter) or up to 12* • 4 humidity probes options • 4 bird scales comm. ports
- 4 bin scales communication ports
- 4 GEV2/S/LED for 120V modules c/w manual overrides for LED lights
- 4 GEV//MS or GE/MS 0-10V modules c/w manual overrides for variable stages or frequency drives
- 2 0-10v outputs for variable stage modules or frequency modules
- 1 communication port for GE-CBW batch feeding module
- X1399 board provides 8 configurable inputs that would increase the capacity for 8 additional or a combination of 8 temperature probes, duration counters (current sensors), or pulse counters (water meters)
- Additional 8 or 16 potentiometer inlets can be added by adding one or two X1205 8 pot board.

NOTE: A relay slave would likely be required

PART #	MODEL	DESCRIPTION
E53-6005	GE-ST40IZK/10	0 VARIABLE, 40 OFF/ON RELAYS, 1 PROBE
E53-6004	GE-ST35IZK/10	0 VARIABLE, 35 OFF/ON RELAYS, 1 PROBE
E53-6003	GE-ST30IZK/10	0 VARIABLE, 30 OFF/ON RELAYS, 1 PROBE
E53-6002	GE-ST25IZK/10	0 VARIABLE, 25 OFF/ON RELAYS, 1 PROBE
E53-6001	GE-ST20IZK/10	0 VARIABLE, 20 OFF/ON RELAYS, 1 PROBE
E53-6000	GE-ST15IZK/10	0 VARIABLE, 15 OFF/ON RELAYS, 1 PROBE
E53-6010	GE-EC	MODBUS MODULE (EC MOTOR)
E53-6011	GE-AC	MODBUS MODULE (AC MOTOR)
E53-6012	GE-MGCB/485	COMM INTERFACE(MGCB TORS485)

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing and



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

iTouch Master Control Models: Base Model

(mostly suited for swine, dairy and some types of poultry)

PART #	MODEL	DESCRIPTION
E53-3010*	GE-430iz/10BMZ	4 variable, 30 off/on relays, 1 probe
E53-2510*	GE-425iz/10BMZ	4 variable, 25 off/on relays, 1 probe
E53-2010*	GE-420iz/10BMZ	4 variable, 20 off/on relays, 1 probe
E53-1510*	GE-415iz/10BMZ	4 variable, 15 off/on relays, 1 probe

*Includes the following input and communication boards x1199 and x1205 potentiometer board.

The base model will then provide for the following possible options by adding the required hardware or items:

- 10 temperature inputs •2 static pressure probes
- 4 duration sensor inputs •2 bin scales
- 4 pulse count (water meters) •8 potentiometer inlet/curtain actuators •2 Humidity probes

Includes 2 communication ports that each port can be used for two of the following 3 choices

- 1-2 bird scales port 1 OR 1-2 light modules port 2
- 1-2 bird scales port 1 OR 1-2 light module port 1 AND 1-2 feed tanks port 2

Note: Two different uses cannot be used on one com port

Additional potentiometer inlets can be added but requires the X1205 pot board, X1276, and X1399 board.

PLEASE CALL EXACON SALES STAFF FOR ASSISTANCE ON PRICING ITOUCH CONTROL SYSTEMS

Control can be ordered from Monitrol pre-programmed for special project with 6 weeks advanced ordering

Charges are applicable for on site set up of ITOUCH controls. Allow 2 weeks notice for set up appointments.

GENIUS iTouch Series cont.

PART #	MODEL	DESCRIPTION
E53-4930	2004/10K	UP TO 10 PROBES BASE MODEL UP TO 16 PROBES** DELUXE MODEL
E53-5402	T15-WD	SAFETY OVER-RIDE - RECOMMEND 4 PER ZONE
E53-4670	RH-3	HUMIDITY PROBE
E53-4677	CRH-3/MGCB	RED WIRE HARNESS - 1 REQD PER HUMIDITY PROBE
E53-9055	750JLPRS	WATER METER C/W PULSE (3/4" CONN.) REPLACEMENT ONLY
E53-9058	750VPD-L	WATER METER C/W PULSE (3/4" CONNECTION)
E53-9057	1000JLPS	WATER METER W/PULSE COUNT (1" CONNECTION)
E53-9899	CONUSB/RJ-45	USB ADAPTER TO RJ45 - ALLOWS DIRECT CONNECTION OF INTERNET TO ITOUCH CONTROL
E53-4679	GE-C02	GE-C02 SENSOR 0-10,000 PPM
E53-4682	GE-LUX-1000	LIGHT SENSOR 0-1000 LUX
E53-4683	GE-WPS-100	WATER PRESSURE SENSOR, 1 YEAR <i>CONDITIONAL</i> WARRRRANTY
E53-4685	DOL-40R	FEED PROXIMITY SENSOR WITH RELAY, 1 YEAR <i>COND.</i> WARRANTY
E53-9282	GE-4V/MS/0-10V	4 OUTPUTS WITH 4 RELAY MODULES. OPTIMIZED ESPECIALLY FOR LED LIGHTS, VARIABLE SPEED MOTORS OR HEATERS C/W MANUAL OVER-RIDES. ONE OR TWO GE-V2/MS REQUIRES ONE COMMUNICATION PORT ON THE ITOUCH CONTROL
E53-9284	GE-V2/MS/0-10V	2 OUTPUTS WITH 2 RELAYS C/W MANUAL OVER-RIDES. SAME FEATURES AS GE-V4/S. ONE OR TWO GEV2-MS/0-10V REQUIRES ONE COMMUNICATION PORT ON THE ITOUCH CONTROL
E53-9775	GE-V1	MODULE - 1 STAGE 10 AMP BOOSTER (1 OR 2)
E53-9780	GE-V2	MODULE - 2 STAGE 10 AMP EACH BOOSTER (1 OR 2)

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing and



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

GENIUS iTouch Series cont.

E53-9895	GE-SP1 REPLACEMENT ONLY-WHILE QTY LAST	STATIC PRESSURE PROBE - UP TO 2 WITH BASE MODEL - UP TO 4 WITH DELUXE MODEL
E53-9898A	CSD-1A	CURRENT SENSOR FOR DURATION COUNTER UP TO 4 ON BASE MODEL, UP TO 6-12* ON DELUXE MODEL NOTE: REQUIRES USE OF MULTI-FUNCTION 8 INPUT X1399 INCLUDED WITH DELUXE MODEL FOR 7-12
E53-9289	GE-V2/S2/120V	VARIABLE SPEED MODULE, 2 PUTPUTS, 10 AMPS C/W MANUAL OVER-RIDES - REQUIRES 1 COM PORT
E53-9270DL	GE-V2/LED	LED LIGHT MODULE, 2 OUTPUTS OF 8 AMPS EACH C/W MANUAL OVER-RIDES. OPERATES MOST DIMMABLE LED LIGHTS
E53-9287	GE-V4/S4/120V	VARIABLE SPEED MODULE, 4 OUTPUTS OF 12 AMPS EACH C/W MANUAL OVER-RIDES. NOTE NOT LIKELY TO OPERATE LED'S SATISFACTORY
E53-9897	X1399/INTERFACE	REQUIRED FOR ITOUCH CONTROL WHEN CONNECTING TO COMPATIBLE EGG COUNTER
E53-4671	GE-HUM+	HUMIDITY SENSOR WITH HARNESS (TWO WIRE) FOR INSIDE OR OUTSIDE HUMIDITY WITH OUTSIDE TEMPERATURE FEATURE
E53-9902	GE-PRESS+	STATIC PRESSURE PROBE - UP TO 2 WITH BASE MODEL - UP TO 4 WITH DELUXE MODEL - NO CALIBRATION NEEDED
E53-5410	PECO	NEMA 4X 1-SPEED THERMOSTAT

EXPANSION RELAY AND VARIABLE SPEED SLAVE MODULE

PART #	MODEL	DESCRIPTION
E53-9881	GE-SL15	15 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES-SMALL BOX
E53-9882	GE-SL20	20 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES-SMALL BOX
E53-3020	GE-SL010Z	10 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES
E53-3021	GE-SL015Z	15 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES
E53-3022	GE-SL020Z	20 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES
E53-3026	GE-SL025Z	25 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES
E53-3027	GE-SL030Z	30 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES
E53-3028	GE-SL040Z	40 OFF/ON RELAY MODULE C/W OFF/ON TOGGLES
E53-3023	GE-SL410Z	10 OFF/ON, 4 VARIABLE MODULE C/W OFF/ON TOGGLES
E53-3024	GE-SL415Z	15 OFF/ON, 4 VARIABLE MODULE C/W OFF/ON TOGGLES
E53-3025	GE-SL420Z	20 OFF/ON, 4 VARIABLE MODULE C/W OFF/OM TOGGLES
E53-3034	GE-SL425Z	25 OFF/ON RELAY, 4 VARIABLE MODULE C/W OFF/ON TOGGLES
E53-3035	GE-SL430Z	30OFF/ON RELAY, 4 VARIABLE MODULE C/W OFF/ON
ONE OF THE ABOVE MODULES CAN BE CONNECTED TO THE DELUXE MODEL BASE MODEL CONTROL MUST HAVE THE OPTIONAL X1276 BOARD TO CONNECT THE ABOVE MODULES ** IF THE ABOVE RELAY MODULES ARE PROVIDING ADDITIONAL POT INLETS TO THE EIGHT PROVIDED IN THE ITOUCH MASTER THAN ADD ONE X1205 8 POT BOARD OR TWO X1205 8 POT BOARD IF 16 INLETS ARE REQUIRED (REFER TO PAGE 4.11B)		

BIRD WEIGHING OPTIONS

PART #	MODEL	DESCRIPTION
E53-9510	OPTI-GAINKIT	LOAD CELL AND PLATFORM KIT FOR BROILERS
E53-9512	OPTI-GAIN-1	OPTIGAIN LOAD CELL MODULE WITHOUT PLATFORM (NO HDWR)
E53-9502	OPTI-GAINKIT/D	OPTIGAIN TURKEY LOAD CELL AND PLATFORM
UP TO 4 OPTIGAIN LOAD CELL/KIT CAN BE CONNECTED TO THE DELUXE MODEL BASE MODEL MUST HAVE THE OPTIONAL X1276 FOR BIRD WEIGHING OPTION		
E53-9517	OPTIGAINBP/KIT	PERCH SCALE FOR LAYERS

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing and



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

FEED BIN SCALES

BASE MODEL CAN OPERATE UP TO TWO BIN SCALES, DELUXE MODEL CAN OPERATE UP TO 4 BIN SCALES

PART #	MODEL	DESCRIPTION
E53-9610SB	FBT-SB	FEED BIN TRANSMITTER - 1 PER BIN REQUIRED
E53-9611	GE-LIM	LIGHTNING ISOLATOR - 1 PER BIN REQUIRED
E53-9615	SB-15K/KIT	SHEAR BEAM LOAD CELL C/W SUPPORT - 1 PER LEG (6 MAX /BIN, 7.5MT MAX LOAD PER LEG)
E53-9608SB	FBT8-SB	FEED BIN TRANSMITTER-1 PER BIN REQ'D (FOR 8 LEG BIN)
E53-9618	DSB-22K/KIT	10MT LOAD CELL C/W SUPPORT - 1 PER LEG
E53-9898A	CSD-1A	CURRENT SENSOR - 1 PER BIN AUGER
E53-9614	SB-15K	SHEAR BEAM LOAD CELL ONLY (6MT)
E53-9619	DSB-22K	LOAD CELL ONLY 10MT

WEATHER STATION

PART #	MODEL	DESCRIPTION
E53-9530	MSTAT-1	WEATHER STATION KIT INCLUDES RAIN DETECTOR, WIND DIRECTION AND SPEED, SUPPORT AND ELECTRONIC NETWORK CARD X1403
E53-9531	RD-1	RAIN DETECTOR ONLY
E53-9532	WS-1	WIND SPEED ONLY
E53-9533	WD-1	WIND DIRECTION ONLY
E53-9534	X1403	NETWORK BOARD FOR IT CONTROL (REQ'D FOR ALL CASES)

NOTE: ABOVE FOR ITOUCH CONTROL ONLY FOR NATURAL CURTAIN LOGIC

OPTIONAL BOARDS

PART #	MODEL	DESCRIPTION
E53-9819	X1200/INPUT-8	8 INPUT BOARD/IT OPTION FOR BASE AND DELUXE MODELS PROVIDES ADDITIONAL INPUTS FOR 4 TEMP PROBES, 2 DURATION COUNTERS, 1 PULSE COUNTER (WATER METER), 1 STATIC PRESSURE INPUT
E53-9878	X1201/1640ER	0-10V 2 OUTPUT BOARD INCLUDED WITH DELUXE MODEL PROVIDES MGCB PORT FOR ADDITIONAL (UP TO TWO GE-V4/S) FOR CONTROL OF LIGHTS OR ADDITIONAL VARIABLE SPEED STAGES ALSO PROVIDES UP TO TWO 0-10V OUTPUTS FOR CHIMNEY DAMPER ACTUATORS, 0-10 HEATERS USE 0-10V GE-V2 OR GE-V4/MS FOR LIGHTS
E53-9822	X1205/POT	8 POT BOARD ONE X1205 INCLUDED WITH BASE AND DELUXE MODELS PROVIDES UP TO EIGHT POT INPUTS FOR INLET ACTUATORS TWO X1205 BOARDS CAN BE ADDED TO A RELAY SLAVE TO ADD UP TO 16 MORE INLET POTENTIOMETER INPUTS
E53-9879	X1276/ COMBOARD8	8 COMM PORT BOARD ONE X1276 BOARD INCLUDED IN DELUXE MODEL PROVIDES FOR THE FOLLOWING USES PER COMM PORT: 1&2 BIRD SCALES, 3&4 BIRD SCALES OR 1 WEATHER STATION AND 1 BIRD SCALE, 8 ADDITIONAL PROBES USING A X1399 BOARD, RELAY MODULE, GE-V2 AND GE-V4 MODULES, 2 ADDITIONAL HUMIDITY PROBES OR 1 HUMIDITY PROBE AND BATCH LOADER, ADDITIONAL 2 BIN SCALES
E53-9896	X1399/ INPUT BOARD-8	8 INPUT BOARD THE DELUXE MODEL INCLUDES 1 X1399 AND THE REQUIRED X1276 BOARD PROVIDES 6 MULTIFUNCTION INPUTS AND 2 MULTIFUNCTION 4-20MA FUNCTIONS. FOR EXAMPLE THESE INPUTS COULD BE USED FOR A COMBINATION OF TEMPERATURE INPUTS, PULSE COUNTS (WATER METERS) DURATION COUNTER (CSD-1A). IT IS POSSIBLE TO ADD UP TO 2 X1399 BOARDS PER ITOUCH

NOTE: IF YOU ADD A X1399 BOARD YOU MUST FIRST HAVE A X1276 BOARD INSTALLED IN THE MASTER CONTROL

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing and availability.



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

ITOUCH UPGRADE DOOR KIT

**IT IS POSSIBLE TO UPGRADE GE-425LS AND GE-430LS TO ITOUCH CONTROLS WITH THE FOLLOWING DOOR KIT AND SLIM BOARD
 ** EXISTING TOGGLES NEED TO BE USED

PART #	MODEL	DESCRIPTION
E53-3029	3412/GE-430i/10	ITOUCH DOOR KIT WITHOUT TOGGLES OR SLIM BOARD
E53-9826	X1416/R	X1416 SLIM BOARD (REQUIRED)
E53-3056	2000/GE-SL415Z	SLAVE (DOOR REPLACEMENT)
E53-9887	3412/GE-420i/10SE	GE-420i (DOOR REPLACEMENT)
E53-9874	3412/GE-415i/10SE	GE-415LSR/GE-420LSR (DOOR REPLACEMENT)
E53-9832	LS75-12	POWER SUPPLY
E53-9826	X1416/R	CONTROL (SLIM BOARD UPGRADE IF NOT V9)
E53-3057	X1415/VAR-4SL	REPLACE X1206 VAR BOARDS
NOTE: IT WILL REQUIRE NEW SET UP OF CONTROL ON SITE. INCLUDE LABOR COST FOR THIS SERVICE.		

REPLACEMENT BOARDS

PART #	MODEL	DESCRIPTION
E53-9831	X1418/VAR2	NEW ITEM 2 VARIABLE BOARD W/CURRENT REPLAY
E53-9816	X1414/AR-RELAY5	NEW ITEM 5 RELAY BOARD W/CURRENT RELAY
E53-9834	X1199/1640ER	SENSOR AND COMM BOARD
E53-9826	X1416/R-CONTROL	OUTPUT SLIM BOARD
E53-9820KIT	X1184/1640ERKIT	5 RELAY BOARD
E53-9828KIT	X1192/1640ERKIT	5 TOGGLE SWITCH BOARD
E53-9821	X1204/TRIAC	2 VARIABLE BOARD
E53-3044	X1415/VAR-4 TOGGL BRD/GE-SLAVE	4 TOGGLE SWITCH BOARD FOR VARIABLES
E53-3040	X1211/C2000A	1 ZONE MICROPROCESSOR BOARD
E53-3041	X1211/C2000AZ	MUTLI-ZONE MICROPROCESSOR BOARD

BATCH FEEDING OPTIONS

PART #	MODEL	DESCRIPTION
E53-9625	GE-CBW	1 REQ'D FOR BATCH FEEDING WEIGHERS FOR COMM. TO ITOUCH
E53-9620	DHBW400	DOUBLE BATCH WEIGHER (APPROX. 38-1/2" X 42-1/2" X 97.5"H) INCLUDES 4 LOAD CELLS AND 1 MOTORIZED DAMPER (400KG CAPACITY)
NOTE: STRONGLY RECOMMENDED TO USE FOR BATCH FEEDING SYSTEMS WITH ITOUCH		

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

i-TOUCH Master Control Models-Deluxe Model Kit

*** Will be installed at Exacon in relays 1-5**

PART #	MODEL#	DESCRIPTION
E53-3030CB/1	GE-430izK/10MZCB	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-3031CB/1	GE-425izK/10MZCB	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-3032CB/1	GE-420izK/10MZCB	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-3033CB/1	GE-415izK/10MZCB	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-6005CB/1	GE-ST40IZK/10	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-6004CB/1	GE-ST35IZK/10	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-6003CB/1	GE-ST30IZK/10	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-6002CB/1	GE-ST25IZK/10	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-6001CB/1	GE-ST20IZK/10	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS
E53-6000CB/1	GE-ST15IZK/10	C/W (1) 5 RELAY BOARD W/CURRENT RELAYS

*** Will be installed at Exacon in relays 1-5 and 6-10**

PART #	MODEL#	DESCRIPTION
E53-3030CB/2	GE-430izK/10MZCB	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-3031CB/2	GE-425izK/10MZCB	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-3032CB/2	GE-420izK/10MZCB	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-3033CB/2	GE-415izK/10MZCB	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-6005CB/2	GE-ST40IZK/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-6004CB/2	GE-ST35IZK/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-6003CB/2	GE-ST30IZK/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-6002CB/2	GE-ST25IZK/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-6001CB/2	GE-ST20IZK/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS
E53-6000CB/2	GE-ST15IZK/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS

GENIUS i-TOUCH 8 Room Multizone

c/w Relay Board with current relay

*** Will be installed at Exacon in relays 1-5, or 1-5 and 6-10**

PART #	MODEL#	DESCRIPTION
E53-3050CB/1	GE-ST10iV8ZP/10	C/W (1) 5 RELAY BOARDS W/CURRENT RELAYS
E53-3050CB/2	GE-ST10iV8ZP/10	C/W (2) 5 RELAY BOARDS W/CURRENT RELAYS

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing and