



254 Thames Road East Exeter, ON. N0M-1S3
 (519) 235-1431 / 1-866-335-1431
 Email: sales@exacon.ca www.exaconinc.ca

J&D INDOOR/OUTDOOR CEILING FAN

THE MODEL CF60 CASABLANCA STYLE CEILING FAN HAS PASSED CUL WATER SPRAY AND CORROSION TESTING. PERFECT FOR GREENHOUSE, AGRICULTURE AND ALL HIGH HUMIDITY AREAS. CF60 MODEL ONLY IS VARIABLE SPEED CONTROLLABLE WITH REVERSE SWITCH ON THE FAN TO CHANGE DIRECTION. **2 YEAR WARRANTY**



115 VOLT C/W 16" CORD, 10" DOWN ROD

DIA.	PART#	SPEED	AMPS	CFM
60"	ECF60A	VARIABLE	0.74	9,415
N/A	ECN5	VARIABLE SPEED CONTROL (UP TO 4 FANS)		

(FOR HIGH HUMIDITY)

J&D WIDE GUARD HAF PANEL FAN

DIRECT DRIVE VARIABLE SPEED 115/230V MOTORS C/W POLY PROP IN FIBERGLASS PANEL FRAME. BUILT IN INDUSTRIAL LOOPS ON THE REAR OF FAN ALLOWS YOU TO ATTACH CHAIN OR CABLE TO HANG FAN STRAIGHT OR AT AN ANGLE.



DIA.	PART#	HP	AMP	CCFM	THRUST CFM
20"	EVPP20F13P	1/3	3.8/1.9	5,180	4070
24"	EVPP24F13P	1/3	3.8/1.9	6,020	4730

J&D SHADE POLE BLOWERS (INFLATION FANS)

DESIGNED FOR USE IN DOUBLE SIDED POLY GREENHOUSES. BOTH MODELS HAVE ADJUSTABLE DAMPER DOORS TO ADJUST AIR FLOW AS POLY EXPANDS IN HEAT OR SMALL HOLES DEVELOP. MOTORS HAVE THERMAL OVERLOAD PROTECTION. **1 YEAR WARRANTY**



PART#	CFM	AMP	FLANGE
EVBM60A-P	60 CFM	0.23	ROUND FLANGE 2-1/8" OPENING
EVMBRKT-RND	-	-	INFLATION FAN BRACKET - ROUND
EVBM148A-P	148 CFM	0.75	SQUARE FLANGE 3-1/4"X2-1/8" OPENING
EVMBRKT-SQ	-	-	INFLATION FAN BRACKET - SQUARE

J&D GALV. PORTABLE DRUM FAN

HEAVY DUTY G90 GALVANIZED HOUSING, POWDER COATED WIRE GUARDS MEETS OSHA REQUIREMENTS. FULLY ASSEMBLED WITH RUBBER FEET AND 8" HARD PLASTIC WHEELS. 10FT-120V CORD C/W OFF/ON SWITCH. **2 YEAR WARRANTY**

DIA.	PART#	HP	AMPS	SPD/DRIVE	CFM
36"	EVI3612WG	1/2	6.1/3.9	1SPD, DD	11,800
42"	EVI4234WG2	3/4	8.9/6.1	2SPD, BD	14,400/10,015
48"	EVI481WG	1	9.0/4.5	1SPD, BD	23,500



J&D WHIRL WIND GALVANIZED BOX FANS

THE HIGH VELOCITY AIR PATTERN GIVES THE GREATEST COOLING EFFECT AT THE LOWEST ELECTRICAL COST. 18 GAUGE GALV. HOUSING, 12 GAUGE HOT DIPPED GALV. WIRE MESH ARE 30% THICKER AND MORE RESISTANT. ALL MODELS COME WITH ATTACHED HANGING BRACKETS FOR QUICK AND EASY INSTALLATION.

DIA.	PART#	VOLT	AMPS	SPD/DRIVE	THRUST CFM
36"	EVG36DM	115/230	6.1/3.9	1SPD / DD	9,680
36"	EVG36VF36GBM	115/230	6.6/3.3	1SPD / BD	9,800
50"	**EVG50	115/230	9.0/4.5	1SPD / BD	20,800



OSHA requires this fan to be mounted 7 feet above the floor.

****NOTE: EVG50 REPLACES EVG48, FRAME SIZE IS THE SAME.**

"BD" BELT DRIVE FANS ARE 24-1/4" DEEP

36" FRAME 40.5" X 40.5"

"DD" DIRECT DRIVE FANS ARE 15-1/2" DEEP

50" FRAME 54.75" X 54.75"

All prices and availability are subject to change without notice due to supplier increases, market conditions, fuel costs, exchange rate fluctuations, and other economic factors; please contact our office for a current quotation to confirm pricing and