

VARIFAN ELECTRONIC TEMPERATURE/ SPEED CONTROLS

ECS CONTROLS

- VARIABLE STAGE ► ALARM CONTACTS ► MOTOR CURVES
 ► HI-LO READINGS ► TEMP RAMPING ► 120/240 VOLT

PART #	MODEL #	DESCRIPTION	PROBE (LENGTH)
E53-8100	ECS-1M	1 STAGE DIGITAL - 1 VARIABLE STAGE (10 AMP.)	2004-1K/30 (30')
E53-8200	ECS-2M	2 STAGE DIGITAL - 1 VARIABLE STAGE (10 AMP.) 1 ON/OFF STAGE-10 AMP. (HEATING OR COOLING)	2004-1K/30 (30')
E53-8300	ECS-3M	3 STAGE DIGITAL - 2 VARIABLE STAGES (6 AMPS EA.) 1 ON/OFF STAGE (10 AMP.) (HEATING OR COOLING)	2004-1K/30 (30')
E53-8400	ECS-4M	4 STAGE DIGITAL - 2 VARIABLE STAGES (6 AMPS EA.) 1 ON/OFF STAGE (10 AMP.) (COOLING, SPRINKLER), 1 ON/OFF STAGE (10 AMP.) (HEATING OR COOLING)	2004-1K/30 (30')
E53-8500	ECS-5M	5 STAGE DIGITAL - 2 VARIABLE STAGES (6 AMP. EA.) 2 ON/OFF STAGES (10 AMP. EA.) (COOLING) 1 ON/OFF STAGE (10 AMP.) (HEATING OR COOLING)	2004-1K/30 (30')
E53-8650	DIP-1/R	DIGITAL INLET POSITIONER - FOR 24V ACTUATOR WITH POTENTIOMETER FEEDBACK, 24 VOLT POWER SUPPLY INCLUDED (MUST BE USED IN CONJUNCTION WITH ONE OR TWO ECS-'M' CONTROLS)	2004-1K (10")

ECS-C CONTROLS

- IMPROVED ENCLOSURE ► LIGHTENING PROTECTION.
 ► UP TO 4 PROBES CAN BE CONNECTED (2 INCLUDED
WITH EACH CONTROL)
 ► 8AMP VARIABLE STAGES ► 10AMP RELAYS
 ► **REQUIRES 240V SUPPLY & 240V VARIABLE STAGE FANS**
 ► **CORE 50 TECHNOLOGY**



PART #	MODEL #	DESCRIPTION	PROBE (LENGTH)
E53-8300C	ECS-3C	2 VARIABLE, 1 OFF/ON RELAY - HEAT & COOL OR MIST (2 PROBES INCLUDED)	2004-10K (10") 2004-10K/30 (30')
E53-8301C	ECS-3C/120	120VOLT - SPECIAL FOR 120VOLT FANS	SAME AS ECS-3C
E53-8500C	ECS-5C	2 VARIABLE, 3 OFF/ON RELAYS - 2 HEAT, 3 COOL 1 MIST (2 PROBES INCLUDED)	2004-10K (10") 2004-10K/30 (30')
E53-8650C	DIP-1C	INLET POSITIONER, 120/240V	2004-10K (10")
E53-3401C	SA-10C	1 STAGE VARIABLE - NON DIGITAL	2004-10K (10")
E53-4670	RH-3	RELATIVE HUMIDITY PROBE **REQUIRES 1 WIRE HARNESS	N/A
E53-4677	CRH-3/MGCB	**RED WIRE HARNESS ("C" CONTROLS)	
E53-4675	CRH-3/ECS	**BLUE WIRE HARNESS ("M" CONTROLS)	
E53-4676	CRH-3/IC	**YELLOW WIRE HARNESS (MSC/IC/LX CONTROLS)	
E53-9849	MM-4	UPLOAD/DOWNLOAD MEMORY STICK	

PROVIDE A MINIMUM OF 1 T15-WD FOR SAFETY BACK-UP ON EACH CONTROL

2 YEAR WARRANTY UNLESS NOTED OTHERWISE

All pricing is subject to change based on potential tariffs or fluctuations in the Canadian dollar. Please call the office for current pricing and availability.

SPECIAL APPLICATION CONTROLS

PART #	MODEL #	DESCRIPTION	PROBE
E53-4825DV	CPS-1H1	PROPORTIONAL THERMOSTAT FOR MODULATING HOT WATER VALVES. C/W SPECIAL PROBE (10° - 70°C OR 50° - 160°F) SAME FEATURES AS CPS-1 (E53-4800)	2004-1KHT (6')
E53-8700	TFD-1/R	1 STAGE VARIABLE 0-10 VOLT FOR 1-10 VOLT DEVICES	2004-1K (10")
E53-8905	THO-2	THO-2 C/W TEMPERATURE PROBE (CONTROLS COMBINATION OF TEMPERATURE AND HUMIDITY) ALSO REQUIRED: HUMIDITY PROBE	2004-1K (10")
E53-4670 E53-4675	RH3 CRH-3/ECS	BLUE CABLE	
E53-4280	PEC-1/KIT	PEC-1 C/W SPS-1 HATCHERY VENTILATION CONTROL MAINTAINS STATIC PRESSURE BY CHANGING FAN SPEED IN EITHER EXHAUST OR INTAKE MODE.	N/A
E53-5130	IC-410-ND Config# 41E01V5	"WATER TROUGH SOW DELIVERY SYSTEM" DELIVERS DESIRED LITRES PER SOW (MAX 150 SOWS PER TROUGH) UP TO 8 TIMES PER DAY. 8 TROUGHS. EXPANDABLE TO 12 (CALL) REQUIRES 1 WATER METER C/W PULSE (SEE PAGE 4.2a)	

HEAT MAT/LAMP CONTROLS

E53-4300	EMC-2	HEAT MAT/LAMP CONTROL (1 PROBE INCLUDED) 2 ZONE, 2 OUTPUTS OF 1000WATTS EACH @ 120V	2004-1K/30
E53-4330	TLC-4200	HEAT MAT/LAMP CONTROL (2 PROBES INCLUDED) 2 ZONE, 2 OUTPUTS OF 16 AMPS EACH	2004-1K
E53-4305	GE-INFRA4	CONTROLS UP TO 4 CRATE'S HEAT LAMPS USING A INFRARED SENSOR CAN ALSO TURN ON AN ADDITIONAL DRYING HEAT LAMP MANUALLY OR WITH OPTIONAL MOTION DETECTOR AND AUTOMATICALLY SHUT OFF ACCORDING TO A TIMER. INCLUDES 4 INFRARED SENSORS (IRS-1)	
E53-4307	IRS-1	INFRARED SENSOR	

POULTRY BIRD SCALES

E53-9500	OPTI-GAIN 4	BIRD WEIGH SCALE MASTER CONTROL 45 DAYS (REQUIRES A MIN. OF ONE PLATFORM SCALE OR UP TO A MAX OF FOUR PLATFORM SCALES (OPTI-GAIN 1)).	CORE 1000
E53-9505	OPTI-GAIN 5	BIRD WEIGH SCALE MASTER CONTROL 250DAYS	CORE 2000
E53-9510	OPTI-GAIN KIT	PLATFORM SCALE C/W HANGING HDWR.	
E53-9520DV	X1152 MD-COM	COMMUNICATION CARD (REQ. IF CONNECTING TO PC)	
E53-9507	OPTI-GAIN 7	TURKEY WEIGH SCALE MASTER CONTROL 250 DAYS	CORE 2000
E53-9502	OPTI-GAINKIT/D	TURKEY PLATFORM SCALE PLATFORM	

METERS

E53-1010	EM10	TEMPERATURE & HUMIDITY METER
E53-1020	EM20	TEMPERATURE & AIRFLOW METER (ft. per min)

*WHILE QUANTITIES LAST



All pricing is subject to change based on potential tariffs or fluctuations in the Canadian dollar. Please call the office for current pricing and availability.

MANUAL VARIABLE SPEED CONTROLS

PART #	MODEL #	DESCRIPTION	
E53-4450C	MVS-1C	MANUAL VARIABLE SPEED CONTROL - 12AMP (INTERNAL TRIM POT)	
E53-4460	MVS-2	MANUAL VARIABLE SPEED CONTROL - 6AMP	
E53-4468	VSD-1MC	VARIABLE SPEED DRIVE - CAN BE CONTROLLED BY A	10AMP
E53-4470	VSD-1MC-20	4-20MA SIGNAL OR 0-10 VOLT c/w MANUAL OVER-RIDES	20AMP
E53-4472	VSD-1MC-40		40AMP
E53-4466	VSD-1C	4-20 OR 0-10V INPUT 10AMPS NO OVER-RIDES	10 AMP

OFF/ON ELECTRONIC DIGITAL TEMPERATURE CONTROLS (ALL RELAYS 10 AMPS)

PART #	MODEL #	DESCRIPTION	PROBE
E53-3600	MST-1/R	ONE STAGE OFF/ON HEATING AND COOLING (1 PROBE INCLUDED)	2004-1KLT
E53-3650	MST-1H1	ONE STAGE OFF/ON HOT WATER HEATING C/W SPECIAL 2004-1KHT PROBE TO READ 10-70°C	2004-1KHT
E53-3640	MST-2B	ONE OFF/ON MISTING, EVAPORATIVE COOLING (1 PROBE INCLUDED) C/W 2 STAGE PROGRESSIVE TIMER. OPTIONAL - RH-3 HUMIDITY PROBE C/W BLUE CABLE MAY BE USED TO DELAY MISTING IF HUMIDITY GETS TOO HIGH	2004-KLT
E53-8850C	MST-5C	FIVE OFF/ON RELAYS - RELAYS 1,2,3 COOL STAGES, RELAYS 4 AND 5 HEAT OR COOL. CAN ALSO BE USED TO RUN UP TO 2 SPD FANS USING RELAYS 1,2 AND RELAYS 3,4 AS LOW SPEED/HIGH SPEED. (1 PROBE INCLUDED - UP TO 4 PROBES POSSIBLE)	2004-10K
EJDDT2	JDDT2	DUAL STAGE DIGITAL THERMOSTAT HEAT OR COOL	

CURTAIN/INLET CONTROLS

PART #	MODEL #	DESCRIPTION	PROBE
E53-4830	CPS-1/L	AIR INLET/CURTAIN CONTROL 1 ZONE (1 PROBE INCLUDED) OPERATES ON TEMP. TIME BASED, DOWN TO -9.9°C. CAN BE USED AS STATIC PRESSURE CONTROL BY ADDING SPS-1 SENSOR	2004-1KLT
E53-4850C	CPS-2C	2 ZONE CURTAIN CONTROL, OPERATES ON TEMP., TIME BASED WITH DELAYS ON BOTH OPEN/CLOSE. (2 PROBES INCLUDED)	2004-10K
E53-8800	CPS-3M/R	2 ZONE CURTAIN CONTROL - C/W HEAT OFF/ON RELAY, TIME BASED WITH DELAY ON BOTH OPEN/CLOSE (2 PROBES INCLUDED)	2004-1K
E53-4270	SPS-1/R	1 STATIC PRESSURE SENSOR (REQUIRES CPS-1/L)	N/A

NOTE: ALSO SEE GENIUS 210, 215, 220 CONTROLS FOR MULTIPLE CURTAIN APPLICATIONS.

VARIFAN COMPONENTS

PART #	MODEL #		DESCRIPTION	Size
E53-4026	.125 MA		FUSE	Power fuse for LX-64X, IC-10, IC-410
E53-4024	.75 AMP		FUSE	Power fuse for VDC24
E53-4030	1 AMP		FUSE	Power fuse for DIP-1
E53-4028	1.5 AMP		FUSE	Power fuse for SVIM-/24
E53-4025	3 AMP		FUSE	Actuator Power Fuse for SVIM-1, DIP, CIP
E53-4020	5 AMP		FUSE	SVIM-1 120V, SLIM BOARD
E53-4032	.250MA		FUSE	.250MA Fuse (GENIUS)
E53-4033	8 AMP		FUSE	GE-4XX var-2 board
E53-4021	10 AMP		FUSE	ECS-1-5M & C Series, MC-22,MST-1H1 MST-2B, EMC-2, CM3-2
E53-4023	15 AMP		FUSE	VPM-1, VPM-2, VSM-2, GE-V2, GE-V1 GE-V4,GE-32,GE-28,MST-1, MVS-1, MVS-2 GE-25, PEC-1
E53-4027	20 AMP		FUSE	TLC-4200, MC-4200SL, CM10-2
E53-4029	FB-1		FUSE BOX	
E50-0621			PLASTIC WATERPROOF CONNECTOR	
E53-3460	2004-100K	ORANGE	NON DIGITAL TEMP. PROBE (SA-10)	10"
E53-4920	2004-1K	RED	DIGITAL TEMP. PROBE (ECS, IC, MST-5, LX) TEMP RANGE: -21 DEG. TO 76 DEG. C, -6 DEG. TO 168 DEG. F	10"
E53-4921	2004-1KLT	BLUE	DIGITAL LOW TEMP. PROBE (MST-1, MST-2B) TEMP RANGE: -10 DEG. TO 41 DEG. C, 13.5 DEG. TO 105.5 DEG. F	10"
E53-4922	2004-1KHT	RED	DIGITAL HOT WATER PROBE (MST-1H1) TEMP RANGE: 10 DEG. TO 70 DEG. C, 50 DEG. TO 160 DEG. F	6FT
E53-4924	2004-1K/30'	RED	30' DIGITAL TEMPERATURE PROBE (ECS, IC, MST-5, LX) TEMP RANGE: -21 DEG. TO 76 DEG. C, -6 DEG. TO 168 DEG. F	30FT
E53-4930	2004/10K	BLACK	PROBE FOR WAVE/GENIUS	10"
E53-4934	2004-10K/30	BLACK	PROBE FOR WAVE/GENIUS	30FT
E53-4925	2004-5K/SV1	RED	SV1 SVIM PROBE	10"
E53-4927DV	2004-5K/SV30		SV1/30 SVIM PROBE	30FT
E53-4915			2 CONDUCTOR, 18 GAUGE SHIELDED WIRE (PER FOOT) (FOR EXTENDING TEMPERATURE PROBES)	
E53-4929	2004-1K/F		FAST READING PROBE (4 TIMES FASTER)	10"
E53-4928	2004-1KX2	RED	DOUBLE LECTURE PROBE	10"

NOTE:

2 YEAR WARRANTY UNLESS NOTED OTHERWISE

MULTIFAN AND MISCELLANEOUS CONTROLS

(1 YEAR WARRANTY)

PART #	MODEL #		DESCRIPTION
E53-5402	T15-WD		SINGLE SPEED THERMOSTAT 10 AMP. 110/220 VOLT
EJDDT2	JDDT2		TWO STAGE DIGITAL THERMOSTAT 10AMP 90-255 VOLT 50/30HZ
E53-5403DV	T10-3		THREE PHASE THERMOSTAT
E53-1025	25		DWYER #25 MARKII MANOMETER 0"-3" S.P.
E53-1026	A-101		RED GAUGE OIL - 3/4 oz BOTTLE
E53-1030	2000-00D		MAGNEHELIC PRESSURE GAUGE (0"-0.25" WC / 0-125 PA)
E53-7676	05-09-060		1/4" CLEAR TUBE (10 FEET)
E53-5410	PECO		NEMA 4X 1SPEED THERMOSTAT

All pricing is subject to change based on potential tariffs or fluctuations in the Canadian dollar. Please call the office for current pricing and availability.

VARIFAN CONTROLS

RECOMMENDED FOR REPLACEMENT ONLY OF EXISTING CONTROLS

PART #	MODEL #	DESCRIPTION	PROBE
E53-4500	MST-3/R	THREE STAGE OFF/ON	
E53-9320	MC-22/R	TWO VARIABLE 6AMP STAGES, 2 OFF/ON 10AMP HEAT/COOL STAGES	3@12"
E53-9000	LX-641-C	ONE INTERNAL RELAY (HEAT, COOL OR SPRINKLER)	3@30'
E53-9005	LX 641-F	EXPANDABLE BY UP TO 4 VARIABLE STAGES (BY ADDING VPM-1, VPM-2 OR VSM-2 MODULES) AND 1 INLET (BY ADDING SVIM-1/24 OR SVIM-1 MODULE)	
E53-9010	LX 642-C	TWO INTERNAL RELAYS (HEAT, COOL, SPRINKLER)	3@30'
E53-9015	LX 642-F	EXPANDABLE UP TO 4 VARIABLE STAGES	
E53-9020	LX 644-C	FOUR INTERNAL RELAYS (HEAT, COOL, 1 SPRINKLER)	3@30'
E53-9025	LX 644-F	EXPANDABLE UP TO 4 VARIABLE STAGES	
E53-9030	LX-644/2-C		
E53-9035	LX-644/2-F		
E53-9110	LX-646/2-C	SIX INTERNAL RELAYS (HEAT, COOL, 1 SPRINKLER)	5@10"
E53-9115	LX-646/2-F	EXPANDABLE UP TO 4 VARIABLE STAGES	
E53-9100	LX-646/4-C		5@10"
E53-9105DV	LX-646/4-F		
E53-9040	VPM-1	ONE VARIABLE STAGE MODULE 6 AMP.	N/A
E53-9045	VPM-2	TWO VARIABLE STAGE MODULE 6 AMP. EACH.	N/A
E53-5260	SVIM-1	DIGITAL INLET MODULE - 110V, FOR USE WITH 110VOLT ACTUATOR	1@30'
E53-5270	SVIM-1/24	DIGITAL INLET MODULE -24V (SUPPLIES 24V OUTPUT TO ACTUATOR)	1@30'
E53-4960	VSM-2	TWO VARIABLE FAN STAGES, 6 AMP C/W TOGGLE OVER-RIDE	
E53-5110	IC-610	INTELLIGENT CONTROL (SPECIFY CONFIGURATION #)	N/A
E53-4940DV	CM10-2	TWO ON/OFF STAGES, 10 AMP. EACH. MAX. 1 1/2 H.P.	N/A
E53-4955	CIP-1	CURTAIN/ INLET POSITIONER, 3 AMP. MODULE	N/A
E53-4963	VSM-2/2	ONE VARIABLE FAN STAGE AT 12 AMP. C/W MAN. OVERRIDE	N/A
E53-4967DV	SPS-24	24VOLT VAC TRANSFORMER ONLY	N/A
E53-4965	VDC-24	24 VOLT TRANSFORMER WITH ENCLOSURE (DC VOLTAGE)	N/A
E53-4970	CM3-2	TWO ON/OF STAGES, 4 AMP. EACH	N/A
E53-4875	R.B.-2	RELAY BOX (25 AMP., 2 H.P.)	N/A
E53-5111	CM-8	CM-8 CONFIGURATION CHIP FOR IC/LX CONTROLS	

FARMQUEST COMMUNICATION SYSTEM (DIRECT WIRED OR WIRELESS)

VIEW AND MANAGE YOUR CONTROLS USING INTERNET(FREE ACCESS) TO ONLINE SERVER

PART #	MODEL#	DESCRIPTION
E53-9154C	WEBGATE C	COMPACT WIRELESS WEBGATE FOR WIRELESS CONNECTION TO FARMQUEST THRU INTERNET SERVICE
E53-9154	WEBGATE 3G/HW	WEBGATE 3G/HW INCLUDES ETHERNET PORT AND NETIN-2 CARD FOR HARD WIRE CONNECTION TO CONTROLS. CONTROLS COMMUNICATION CARDS
E53-9162	DOORLOCK/IDC	ELECTRICAL DOOR ACCESS 5 RFID
E53-9054	RF-P4	MULTI PURPOSE 4 INPUT MODULE (WIRELESS)

WI FARM 3G ANTENNAS & ANTENNA CONTROL CARDS FOR WIRELESS SYSTEM

PART #	MODEL#	DESCRIPTION
E53-9155	RF-IN1	ANTENNA CARDS FOR CORE 100 CONTROLS (ECS-C, GE-25, 28, L2)
E53-9156	RF-IN2	ANTENNA CARDS FOR CORE 1000/2000 CONTROLS (GENIUS, OPTIGAIN)
E53-9157	RF-XTEND	ANTENNA FOR EXTERIOR MOUNT - USED TO EXTEND RANGE OF RF ACCESS ANTENNA'S OR AROUND OBSTRUCTIONS.
E53-9158	RF-ACCESS	WIRELESS SYSTEM ANTENNA - USED TO SEND SIGNAL THRU WALLS AND BETWEEN BUILDINGS UP TO 1600FT BETWEEN EACH ANTENNA (DISTANCE BASED ON DIRECT VIEW LINE OF SIGHT.)

COMMUNICATION CARDS FOR DIRECT WIRE SYSTEM

PART #	MODEL#	DESCRIPTION
E53-9797	X1264/COM	COM CARD FOR GENIUS GE25, GE28, GE-6X
E53-9830	X1202/1640ER	COM CARD FOR: CORE 1000, 2000, GENIUS 4X, 4XLS AND AGRI-MANAGER CONTROLS
E53-9160DV	NETIN-2	COM CARD FOR: CORE 50, 100, GE-L2, ECS-C
E53-9520DV	X1152 MDCOM	COM CARD FOR OPTIGAINS

FARM SITE COMMUNICATION SYSTEM- USING SOFTWARE ON PERSONAL PC

3G "WI FARM" WIRELESS COMMUNICATION SYSTEM

PART #	MODEL#	DESCRIPTION
E53-9152DV	RAN-1	RADIO ACCESS NETWORK ANTENNA USB KEY FOR PC

FARM-SITE SOFTWARE FOR YOUR PC IS FREE

****NOTE: CONTROLS MUST HAVE RF-IN OR RF-IN2 WIRELESS CARDS TO COMPLETE SYSTEM**