



by **Optimizing Bird Weight gain** of your production using the easy to install **GE-OPTIGAIN1**

Simply connect this module to one of many **GENIUS** controllers, and start collecting bird weights. This allows you to:


- » Constantly **track bird weights accurately**, providing you with an important management tool for optimizing weight gain
- » **Predict bird health issues**, reducing medical costs and bird mortality
- » **Reduce bird stress and labor costs** by eliminating manual weighing
- » Helps birds **attain target shipping weight**
- » **Access your data 24/7** with the **FarmQuest** online service and make informed decisions



Turkey scale



Complete **CONTROL** of your data from **ANYWHERE, 24/7**



Choose FarmQuest! Remotely accessible 24/7 Why?

- » **Validate** your bird weights
- » **Obtain** your number of weightings
- » **See** your average weight of the day
- » **Evaluate** your weight gains
- » **Observe** your homogeneity

The flexibility to send your data or even give access to:

- » **Yourself**
- » The **farm manager**
- » Your **buyers**
- » **Anyone** you think should be involved



COMPATIBLE WITH:
FarmQuest
BY MONITROL
LIVESTOCK MANAGEMENT
www.farmquest.com



EXACON INC
254 Thames Road East
Exeter, On
1-866-335-1431
sales@exacon.ca
www.exaconinc.ca

WebGate 3G / FarmQuest

Wi Farm Wireless Network & Hardwire Connection


WebGate 3G



- Your connection to the **FarmQuest** server
- **WebGate 3G** connects your controls to the Internet using wired (/HW) and / or wireless (/RF) connection
- Very easy to install
- Using antennas below, the **WebGate 3G** can connect to controls and create a **Wi Farm** network



RF-IN : Antenna for CORE-50 / 100 Controls



RF-IN2 : Antenna for CORE-1000 / 1500 / 2000 Controls



RF-XTEND : Extends exterior range of wireless network

RF-ACCESS : Allows for easy wireless access into buildings

- 1600ft (500m) range between each antenna
- Signal can be relayed from one antenna to another up to 5 times

by:





www.m2mtelesystems.com
1291 Ampère
Boucherville (QC) J4B 5Z5
Tel: (450) 641-4810
Fax: (450) 641-4631



Management Software For Livestock Buildings

Communicate With Your Controls Using The Internet

-  **Controls** View your controls using the internet
-  **Graphs** Analyse your results with graphs
-  **Reports** Create and send report by email
-  **System View** Overview of system
-  **Security** Manage access and cameras
-  **Tools** Customize your FarmQuest



Example: graph screen

Userfriendly interface allows you to easily manage your equipment (Ventilation, scales, feed, water counter, access, etc...)

With Farmquest and the access control system, you are in control of your biosecurity.

by:



www.m2mtelesystems.com
1291 rue Ampère
Boucherville (QC) J4B 5Z5
Tel: (450) 641-4810
Fax: (450) 641-4631

Varifan®

ECS-3C

3-STAGE VENTILATION CONTROL **2 Variables - 1 On / Off (Cool / Heat or Mist)**

Improved
Design!



COMPATIBLE WITH:



Online monitoring
and management



Management software



FEATURES:

C Series

- Most effective lightning protection
- Extended temperature range
- Extended supply voltage range
- Radio interference filter
- Alarms, Hi/Lo, loss of power & defective control
- Maintain settings after power loss
- Two-year limited warranty
- Up to four-probe average temperature
- Outside temperature probe
- Timer on minimum speed
- Temperature and minimum speed ramping
- Controls humidity with humidity probe (optional)
- Choice of 9 motor curves
- Full torque start (4 sec.)
- Hi / Lo temperature recall
- Heaters run time record
- 5-digit LED display
- Optional inlet positioning with DIP-1C

Varifan®

Manufactured by **Monitrol Inc.** Tel.: 450-641-4810
1291 Ampere St. Fax: 450-641-4631
Boucherville (QC) J4B 5Z5 Email: monitrol@monitrol.com
Canada www.varifan.com

Varifan®

ECS-5C

5-STAGE VENTILATION CONTROL **2 Variables - 3 On / Off (Cool / Heat or Mist)**

Improved Design!



COMPATIBLE WITH:



Online monitoring and management



Management software



FEATURES:

C Series

- Most effective lightning protection
- Extended temperature range
- Extended supply voltage range
- Radio interference filter
- Alarms, Hi/Lo, loss of power & defective control
- Maintain settings after power loss
- Two-year limited warranty
- Up to four-probe average temperature
- Outside temperature probe
- Timer on minimum speed
- Temperature and minimum speed ramping
- Controls humidity with humidity probe (optional)
- Choice of 9 motor curves
- Full torque start (4 sec.)
- Hi / Lo temperature recall
- Heaters run time record
- 5-digit LED display
- Optional inlet positioning with DIP-1C






Varifan®

Manufactured by **Monitrol Inc.** Tel.: 450-641-4810
1291 Ampere St. Fax: 450-641-4631
Boucherville (QC) J4B 5Z5 Email: monitrol@monitrol.com
Canada www.varifan.com

All descriptions and characteristics can be changed without notice or obligations.

ECS-5C_V4_E (10/01/2012)

ECS-M SERIES COMPARATIVE TABLE

					
Control	ECS-1M	ECS-2M	ECS-3M	ECS-4M	ECS-5M
Temperature probe inputs *	1	1	1	1	1
Relay outputs	0	1	1	2	3
Variable outputs	1	1	2	2	2
Alarm relay with delay	yes	yes	yes	yes	yes
PC Port	1	1	1	1	1
Casing dimensions	8¼" X 4" X 8" (21,2 X 10,2 X 20,3 cm)	8¼" X 4" X 8" (21,2 X 10,2 X 20,3 cm)	8¼" X 4" X 8" (21,2 X 10,2 X 20,3 cm)	8¼" X 4" X 8" (21,2 X 10,2 X 20,3 cm)	8¼" X 4" X 8" (21,2 X 10,2 X 20,3 cm)

* Optional humidity probe inputs available.