


NEW

58" AirBlaster - Precision Velocity


**3 Year
Warranty
on ENTIRE
fan**

4 Louver Air Blaster
on Page 5.10b

3 Louver Uni-Directional

Part#	Size	Ph	Spd	Thrust CFM	CFM/ Watt
EVAB58L3S3221AG-CK	58"	1	1/Var^	100% 41,521	15.3
				90% 37,129	19.3
				80% 32,971	24.4
				70% 28,763	32.2
				60% 24,795	44.1
				50% 20,332	59.9
				40% 16,421	87
EVAB58L3S3223BG-CK	58"	3	1/Var^	100% 41,265	15.6
				90% 36,703	19.5
				80% 33,043	24.4
				70% 28,941	32.2
				60% 24,824	43.8
				50% 20,704	61.4
				40% 17,420	93.7
EVAB58L3S3223CG-CK	58"	3	1/Var^	100% 41,480	15.2
				90% 37,532	19.1
				80% 32,855	23.9
				70% 28,873	31.4
				60% 24,714	42.2
				50% 20,119	57.6
				40% 16,688	80.6

Housing

- Rugged, corrosion resistant poly with UV inhibitor
- Precision injection molded

Motor Frame

- 304 stainless steel

PM Direct Drive Motor

- Internal Motor Drive
- Provides soft starts
- Enables variable speed
- Allows for precise and uniform speed control
- Surge protection
- Overload protection
- Thermal foldback protection
- Industrial cast-aluminum housing
- IP65 rated, CURUS Approved

Blade

- 3 glass filled poly composite blades

All pricing is subject to change based on potential tariffs or fluctuations in the Canadian dollar. Please call the office for current pricing and availability.

NEW

58" AirBlaster - Precision Velocity




4 Louver Bi-Directional

OSHA requires this fan to be mounted a minimum of 7ft above the floor



60ft apart running at 100%

Slow down the fan to speed up energy savings



30ft apart running at 50% will provide the near equivalent amount of air movement as the 60ft spacing running at 100% while using only 1/4th the energy

Part#	Size	Ph	Spd	Thrust CFM	CFM/Watt
EVAB58L4S3221AG-CK	58"	1	1/Var	100% 40,423	14.2
				90% 36,000	18.2
				80% 31,888	23.2
				70% 28,053	30.3
				60% 23,905	41.2
				50% 19,821	57.4
EVAB58L4S3223CG-CK	58"	3	1/Var	40% 15,722	81.1
				100% 41,004	15.4
				90% 37,142	18.6
				80% 32,921	24.0
				70% 28,776	31.0
				60% 24,537	42.0
				50% 20,233	58.6
				40% 16,719	84.7

The AirBlaster Recirculation Fan uses a maintenance free direct drive permanent magnet motor. IP65 rated, CURUS Approved.

It eliminates the need for greasing bearings and changing belts. The housing is made of strong poly while the frame is all stainless steel preventing rust and corrosion in any environment.

The AirBlaster Recirculation Fan easily mounts to chains hung from the ceiling. This is the perfect fan for low profile ceilings. The angle of the fan gives us more space to mount and still be OSHA compliant.

What happens when you only apply a certain percentage power to the AirBlaster?

You save energy!

This is especially beneficial for minimum winter ventilation. Still get the airflow you need, but save on your energy bill. No dead spaces at the target level!