



HOG HEAT SUPERIOR


Saving energy and optimising the climate inside a hog house are top priorities for every pig farmer. The Hog Heat Superior heater by Multiheat is a top-quality, compact and powerful solution.



ROBUST A-CLASS QUALITY FAN



HIGH AIR CAPACITY OF 1.600 m³/hr



DOUBLE EPOXY COATING

PART #	DESCRIPTION
E68-8754	HOG HEAT SUPERIOR 240V
E68-8754-120	HOG HEAT SUPERIOR 120V

OPTIONAL

E68-8728	DN 15X2000MM HOSE (Require 2 per heater) HANGING HARDWARE SUPPLIED SEPARATELY
----------	--

TECHNICAL DATA

WATER SUPPLY/RETURN	AMBIENT TEMPERATURE	OUTPUT / WATER FLOW / RESISTANCE
90/70 °C - 194/158 °F	20 °C - 68 °F	16 kW / 0,7 m ³ /h / 7,8 kPa - 54.600 BTU / 3,1 gpm / 31 wc
90/70 °C - 194/158 °F	30 °C - 86 °F	13 kW / 0,6 m ³ /h / 5,5 kPa - 44.360 BTU / 2,6 gpm / 22 wc
80/65 °C - 176/149 °F	20 °C - 68 °F	14 kW / 0,9 m ³ /h / 10,6 kPa - 47.770 BTU / 4,0 gpm / 43 wc
80/65 °C - 176/149 °F	30 °C - 86 °F	11 kW / 0,7 m ³ /h / 7,1 kPa - 37.530 BTU / 3,1 gpm / 29 wc